

County Surveyor's Record, Douglas County, Oregon

South Boundary of T. 29 S., R. 3 E.

CHAINS

A Cedar, 5 ins. in diam., bears S.76\*W., 29 lks. dist., marked T 30 S R 3 E S 4 B T.

A Fir, 16 ins. in diam., bears N.43\*W., 78 lks. dist. marked T 29 S R 3 E S 33 B T.

Land.:Rolling & rough, mountains.

Soil: Sandy Loam & rocky. 2nd rate.

Timber: Fir, pine & cedar.

Undergrowth: Small fir & pine, buck brush, & huckleberry.

West, bet. secs. 4 & 33.

Over mountainous land, through heavy timber and medium undergrowth.

Asc. slightly over S. slope.

1.50 Spur, slopes SW., desc. 500 ft. over W. slope.

19.20 Flat creek. 15 lks. wide, course S., asc. 330 ft. over E. slope to

40.00 Set an iron post, 3 ft. long, 1 in. in diam., 30 ins. in the ground, for  $\frac{1}{4}$  sec. cor. with brass cap marked

$$\frac{1}{4} \begin{array}{r} S 33 \\ S 4 \end{array}$$

From which

A Fir, 26 ins. in diam., bears N.4\*E., 43 lks. dist. marked  $\frac{1}{4}$  S 33 B T.

A Fir, 32 ins. in diam., bears S.10\*W., 5 lks. dist. marked  $\frac{1}{4}$  S 4 B T.

Asc. 355 ft. over E. slope.

51.00 Leave green timber. enter a burn, bears N. & S.,

73.75 Ridge & Forest Service Trail. bears N. & S., desc. 280 ft. over rocky W. slope to

80.00 Enter green timber, bears N. & S.

Set an iron post, 3 ft. long, 2 ins. in diam., 28 ins. in the ground, with brass cap marked

$$\begin{array}{r} T 29 S | R 3 E \\ S 32 | S 33 \\ S 5 | S 4 \\ T 30 S \\ 1927 \end{array}$$