

County Surveyor's Record, Douglas County, Oregon

South Boundary of T. 29 S., R. 3 E.

CHAINS	
	<p>From which</p> <p>A Fir, 12 ins. in diam., bears N.8½*E., 328 lks. dist., marked T 29 S R 3 E S 33 B T.</p> <p>A Fir, 20 ins. in diam., bears S.14*E., 102 lks. dist., marked T 30 S R 3 E S 4 B T.</p> <p>A Fir, 16 ins. in diam., bears S.6*W., 96 lks. dist., marked T 30 S R 3 E S 5 B T.</p> <p>A Fir, 36 ins. in diam., bears N.3*W., 261 lks. dist., marked T 29 S R 3 E S 32 B T.</p> <p>Land; Mountainous.</p> <p>Soil; Sandy loam & rocky. 2nd rate.</p> <p>Timber; Fir & pine.</p> <p>Undergrowth; Huckleberry, buck brush, vine maple, & small pine.</p> <hr/> <p>West, bet. secs. 5 & 32.</p> <p>Over Mountainous land, through medium timber and medium undergrowth.</p> <p>Desc. 900 ft. over broken W. slope.</p>
27.40	Spring branch, 2 lks. wide, course S., asc. 150 ft. over SE. slope to
40.00	Set an iron post, 3 ft. long, 1 in. in diam., 32 ins. in the ground, for ¼ sec. cor with brass cap marked
	$\frac{\frac{1}{4} S 32}{S 5}$
	<p>From which</p> <p>A Fir, 20 ins. in diam., bears S.13*E., 159 lks. dist., marked ¼ S 5 B T.</p> <p>A Cedar, 24 ins. in diam., bears N.80*W., 102 lks. dist., marked ¼ S 32 B T.</p> <p>Asc. 25 ft. over SE. slope.</p>
42.50	Top of asc. thence over a bench, bearing NE. & SW.
52.50	Desc. 400 ft. over broken NW. slope to
80.00	Set an iron post, 3 ft. long, 2 ins. in diam., 30 ins. in