

County Surveyor's Record, Douglas County, Oregon

South boundary of T. 29 S. R. 3 E.

CHAINS

the ground, for cor. of secs. 5, 6, 31 & 32, with brass cap marked

T 29 S R 3 E  
 S 31 | S 32  
 S 6 | S 5  
 T 30 S  
 1927

From which

A Fir, 6 ins. in diam., bears N.6°E., 61 lks.,  
 dist., marked T 29 S R 3 E S 32 B T.

A Fir, 5 ins. in diam., bears S.60°E., 28 lks.,  
 dist. marked T 30 S R 3 E S 5 B T.

A Fir, 30 ins. in diam., bears S.54°W., 95 lks.,  
 dist., marked T 30 S R 3 E S 6 B T.

A Fir, 34 ins. in diam., bears N.71°W., 109 lks.,  
 dist., marked T 29 S R 3 E S 31 B T.

Land., Mountainous & Rolling.

Soil., Sandy loam & rocky. 2nd rate.

Timber., Fir, pine & cedar.

Undergrowth., Small fir & pine, huckleberry, salal and  
 Vine maple.

West, bet. secs. 6 & 31.

Over mountainous land, through scattering timber and  
 dense undergrowth.

Desc. 60 ft. over NW. slope.

22.00 Foot of desc. on N. slope asc. 80 ft. over NE. slope.

30.00 Spur, slopes N., enter heavy timber, bears NW. & SE.,  
 desc. 15 ft. over NW. slope to

40.00 Set an iron post, 3 ft. long. 1 in. in diam., 30 ins.  
 in the ground, for  $\frac{1}{4}$  sec. cor. with brass cap marked

$\frac{1}{4}$  S 31  
 S 6

From which

A Fir, 42 ins. in diam., bears N.63°E., 58 lks.,  
 dist., marked  $\frac{1}{4}$  S. 31 B T.

A Fir, 30 ins. in diam., bears S.53°W., 38 lks.,  
 dist., marked  $\frac{1}{4}$  S 6 B T.