

County Surveyor's Record, Douglas County, Oregon

East. Boundary of T. 29 S., R. 3 E.

CHAINS

North, bet. secs. 19 & 24.

Over mountainous land, through heavy timber & medium undergrowth.

2.00 Asc. 40 ft. over SE. slope.  
 Spur, slopes, E., desc. 100 over N. slope.  
 8.17 Spring branch, 5 lks. wide, course E., asc. 230 ft. over S. slope.

23.00 Spur, slopes NE., desc. 125 ft. over NE. slope to

40.00 Set an iron post, 3 ft. long, 1 in. in diam., 28 ins. in the ground, for  $\frac{1}{4}$  sec. cor. with brass cap marked

$\frac{1}{4}$   
 S 24 | S 19  
 1927

From which

A Fir, 16 ins. in diam., bears N.12\*E., 107 lks., dist., marked  $\frac{1}{4}$  S 19 B T.

A Fir, 15 ins. in diam., bears S.51 $\frac{1}{2}$ \*W., 42 lks., dist., marked  $\frac{1}{4}$  S 24 B T.

Desc. 75 ft. over NE. slope.

54.76 Spring branch, 3 lks. wide, course E., asc. 35 ft. over SE. slope.

60.00 Spur, slopes NE., desc. 120 ft. over broken NE. slope.

72.50 S. bank of Foster Creek, 1.00 chs. wide, course SE., asc. 25 ft. over S. slope to

80.00 Set an iron post, 3-ft. long, 2 ins. in diam., 24 ins. in the ground, for cor. of secs. 13,18,19 & 24. with brass cap marked

T 29 S.  
 R 3 E R 4 E  
 S.13 | S 18  
 S 24 | S 19  
 1927

From which

A Pine, 26 ins. in diam., bears N.60\*E., 98 lks, dist. marked T 29 S R 4 E S 18 B T.

A Fir, 18 ins. in diam., bears S.34 $\frac{1}{2}$ \*E., 117 lks., dist., marked T 29 S R 4 E S 19 B T.