

## County Surveyor's Record, Douglas County, Oregon

East Boundary of T. 29 S., R. 3 E.

CHAINS

4 ft. base,  $1\frac{1}{2}$  ft. high around the post, for  $\frac{1}{4}$  sec. cor.  
with brass cap marked

$$\begin{array}{c} \uparrow \\ S\ 1\ | S\ 6 \\ 1927 \end{array}$$

From which

A Fir, 28 ins. in diam., bears S.30\*E., 60 lks..  
dist., marked  $\frac{1}{4}$  S 6 B T.

A Fir, 28 ins. in diam., bears S.35\*W., 75 lks..  
dist., marked  $\frac{1}{4}$  S 1 B T.

Desc. 390 ft. over broken NW. slope.

48.00

Leave thicket.

57.00

Enter grassy opening, bears NE. &amp; SW.

64.20

Creek, 10 lks. wide, course NE.

65.50

Asc. 45 ft. over rocky SE. slope. Enter stunted timber  
and light undergrowth, bears NE. & SW.

70.25

Rock spur, slopes SE.. desc. slightly over rocky E.  
slope to

80.00

Set an iron post, 3 ft. long, 3 ins. in diam., 10 ins. in  
the ground to bed rock, and build a mound of stone,  
 $4\frac{1}{2}$  ft. base, 2 ft. high, around the post, for cor. of  
Tps. 28 & 29 S., Rs. 3 & 4 E., with brass cap marked

$$\begin{array}{c} T\ 28\ S \\ R\ 3\ E\ R\ 4\ E \\ S\ 36\ | S\ 31 \\ S\ 1\ | S\ 6 \\ 1927 \end{array}$$

From which

A Hemlock, 20 ins. in diam., bears N.78\*E., 93 lks..  
dist., marked T 28 S R 4 E S 31 B T.

A Fir, 22 ins. in diam., bears S.57\*E., 195 lks..  
dist., marked T 29 S R 4 E S 6 B T.

A Fir, 12 ins. in diam., bears S.34\*W., 149 lks..  
dist., marked T 29 S R 3 E S 1 B T.

A Pine, 15 ins. in diam., bears N.41\*W., 28 lks..  
dist., marked T 28 S R 3 E S 36 B T.

Land., Mountainous.