

County Surveyor's Record, Douglas County, Oregon

East Boundary of T. 29 S., R. 3 E.

CHAINS

Soil., Sandy loam & rocky. 2nd & 3rd rate.

Timber., Fir, pine, hemlock & larch.

Undergrowth., Small fir, huckleberry & vine maple.

North Boundary of T. 29 S., R. 3 E.

West, on a random line, setting temp. $\frac{1}{4}$ sec. cors.

alternatley at intervals of 40.00 chs.

482.33

Intersect N. & S. line 91 lks., N. of the cor. of Tps. 28 & 29 S., Rs. 2 & 3 E., hereinbefore described.

From the opr. of Tps. 28 & 29 S., Rs. 3 & 4 E., described on the preceding page of these notes.

S.89*54'W., on a true line bet. secs. 1 & 36.

Over mountainous land, through heavy timber & medium undergrowth.

Asc. 1300 ft. over broken SE. slope to

40.00

Set an iron pest, 3 ft. long, 1 in. in diam., 30 ins. deep in small broken rock between boulders, for $\frac{1}{4}$ sec. cor. with brass cap marked

$\frac{1}{4}$ S 36
S 1
1927

From which

A Fir, 14 ins. in diam., bears N.25*E., 77 lks., dist., $\frac{1}{4}$ S 36 B T.

A Fir, 10 ins. in diam., bears S.26*W., 44 lks., dist., marked $\frac{1}{4}$ S 1 B T.

Asc. 350 ft. over broken SE. slope.

52.00

Top of a nearly perpendicular cliff, 100 ft. high, and ridge. bears N. & S., sloping N. at this point., desc. 125 ft. over rocky NW. slope.

62.00

Foot of desc. on N. slope, asc. 170 ft. over NE. slope.

79.25

Spur, slopes N., desc. 15 ft. over NW. slope to

80.00

Set an iron post, 3 ft. long, 2 ins. in diam., 28 ins. in the ground, for cor. of secs. 1, 2, 35 & 36 with brass cap marked--