

County Surveyor's Record, Douglas County, Oregon

North Boundary of T. 29 S., R. 3 E.

CHAINS S.89\*54'W., on a true line bet. secs. 5 & 32.  
 Over mountainous land, through heavy timber and medium undergrowth.  
 Asc. 15 ft. over rocky SE. slope.  
 0.60 Rock spur, slopes S., desc., 110 ft. over rocky SW. slope.  
 4.00 Draw, drains S., asc., 330 ft. over rocky SE. slope.  
 14.15 Rocky spur, slopes S., desc. 490 ft. over rocky W. slope.  
 27.00 Draw, drains SW., asc. 325 ft. over SE. slope.  
 36.00 Spur, slopes S., desc. 75 ft. over NW. slope to  
 40.00 Set an iron post, 3 ft. long, 1 in. in diam., 28 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap marked

$\frac{1}{4}$  S 32  
 $\frac{1}{4}$  S 5  
 1927

From which

A Fir, 48 ins. in diam., bears N.6\*W., 35 lks.,  
 dist., marked  $\frac{1}{4}$  S 32 B T.

A Pine, 40 ins. in diam., bears S.18\*E., 96 lks.,  
 dist., marked  $\frac{1}{4}$  S 5 B T.

Thence over S. slope.

42.50 Spur, slopes SW., desc. 580 ft. over SW. slope to  
 66.00 Spring branch, 2 lks. wide, course SW., desc. 290 ft. over SW. slope to  
 80.00 Set an iron post, 3 ft. long, 2 ins. in diam., 30 ins. in the ground. for cor. of secs. 5,6,31 & 32 with brass cap marked

T 28 S R 3 E  
 S 31 | S 32  
 S 6 | S 5  
 T 29 S  
 1927

From which

A Pine, 30 ins. in diam., bears N.36 $\frac{1}{2}$ \*E., 94 lks.,  
 dist., marked T 28 S R 3 E S 32 B T.

A Fir, 30 ins. in diam., bears S.61\*E., 46 lks.,  
 dist., marked T 29 S R 3 E S 6 B T.

A Fir, 28 ins. in diam., bears S.5\*W., 114 lks.,  
 dist., marked T 29 S R 3 E S 6 B T.