

## County Surveyor's Record, Douglas County, Oregon

North Boundary of T. 29 S., R. 3 E.

CHAINS

Soil., Rocky, 3rd rate.

Timber., Fir, pine &amp; cedar.

Undergrowth., Huckleberry, cedar, small fir &amp; pine.

---

 Subdivision of T. 29 S., R. 3 E.
 

---

From the cor. of secs. 1, 2, 35 & 36, on the S. Bdy of the township hereinbefore described.

N.0°01'W., bet. secs. 35 &amp; 36.

Over mountainous land, through heavy timber & medium undergrowth.

Asc. 170 ft. over S. slope.

8.80 Spur, slopes SE., desc. 360 ft. over NE. slope.

32.90 Spring branch,  $\frac{1}{2}$  lk. wide, course NE., asc. 80 ft. over SE., slope to40.00 Set an iron post, 3 ft. long, 1 in. in diam., 27 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap marked
$$\begin{array}{c} \frac{1}{4} \\ \text{S } 35 \text{ | } \text{S } 36 \\ 1927 \end{array}$$

From which

A Fir, 20 ins. in diam., bears N.51°E., 52 lks., dist., marked  $\frac{1}{4}$  S 36 B T.

A Pine, 50 ins. in diam., bears N.62°W., 30 lks., dist., marked  $\frac{1}{4}$  S 35 B T.

Thence over E. slope.

47.00 Desc. 160 ft. over NE. slope.

52.50 Rabbit Ears Creek, 8 lks. wide, course E., asc., 655 ft. over S. slope.

68.60 Spur, slopes SE., desc 335 ft. over NE. slope to

80.00 Set an iron post, 3 ft. long, 2 ins. in diam., 26 ins. in the ground, for cor. of secs. 25, 26, 35 &amp; 36, with brass cap marked

$$\begin{array}{c} \text{T } 29 \text{ S } \text{ R } 3 \text{ E} \\ \text{S } 26 \text{ | } \text{S } 25 \\ \text{S } 35 \text{ | } \text{S } 36 \\ 1927 \end{array}$$