

County Surveyor's Record, Douglas County, Oregon

Subdivision of T. 29 S., R. 3 E.

CHAINS	From which
	A Fir, 14 ins. in diam., bears N.79*E., 37 lks., dist., marked T 29 S R 3 E S 25 B T.
	A Fir, 12 ins. in diam., bears S.58*E., 154 lks., dist., marked T 29 S R 3 E S 36 B T.
	A Fir, 20 ins. in diam., bears S.25*W., 49 lks., dist., marked T 29 S R 3 E S 35 B T.
	A Fir, 24 ins. in diam., bears N.59*W., 23 lks., dist., marked T 29 S R 3 E S 26 B T.
	Land., Mountainous.
	Soil., Sandy loam and rocky, 2nd & 3rd rate.
	Timber., Fir, pine & cedar.
	Undergrowth., Snow brush, huckleberry and vine maple.
	_____
	East, on a random line bet. secs. 25 & 36.
40.00	Set temp $\frac{1}{4}$ sec. cor.
79.76	Intersect N. & S line 28 lks. N. of cor. of secs. 25, 30, 31 & 36.
	Thence
	N.89*48'W., on a true line.
	Over mountainous land, through medium timber & medium undergrowth.
	Desc. 80 ft. over SW. slope.
7.00	Draw, drains SW., asc. 160 ft. over SE. slope.
18.65	Spur, slopes SW., desc. 380 ft. over NW. slope.
36.55	Spring branch, 5 lks. wide course S., asc. 70 ft. over E. slope to
39.88	Set an iron post, 3 ft. long, 1 in. in diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked
	$\begin{array}{r} S\ 25 \\ \frac{1}{4} S\ 36 \\ \hline 1927 \end{array}$
	From which
	A Hemlock, 14 ins. in diam., bears S.24*W., 55 lks., dist., marked $\frac{1}{4}$ S 25 B T.