

County Surveyor's Record, Douglas County, Oregon

Subdivision of T. 29 S., R. 3 E.

CHAINS

Fir, 10 ins. in diam., bears N.46*W., 29 lks.,
dist., marked $\frac{1}{4}$ S 36 B T.

Thence over the top of a spur, sloping S.

42.00 Desc., 80 ft. over SW. slope.

52.45 Hersberger Creek, 28 lks. wide, course S., asc. 495 ft.
over NE. slope to

79.76 The cor of secs., 25, 26, 35 & 36.

Land., Mountainous.

Soil., Sandy loam & rocky, 2nd & 3rd rate.

Timber., Fir, pine & cedar.

Undergrowth., Willow, huckleberry, vine maple, small fir
and pine.

N.0*01'W., bet. secs. 25 & 26.

Over mountainous land, through medium timber & medium
undergrowth.

Desc. 145 ft. over NE. slope.

6.00 Creek, 5 lks. wide, course E., asc. 320 ft. over S. & SE.
slope,

16.60 Spur, slopes SE., desc. 460 ft. over NE. slope.

32.97 Hersberger Creek, 15 lks. wide, course SE., asc. 355 ft.
over rocky S. slope to

40.00 Set an iron post, 3 ft. long, 1 in. in diam., 18 ins. in
the ground to bed rock, in a mound of stone, 2 ft. base,
1 ft. high, for $\frac{1}{4}$ sec. cor with brass cap marked

$\frac{1}{4}$
S 26 | S 25
1927

From which

A Fir, 14 ins. in diam., bears N.80*E., 11 lks.,
dist., marked $\frac{1}{4}$ S 25 B T.

A Cedar, 14 ins. in diam., bears S.60*W., 4 lks.,
dist., marked $\frac{1}{4}$ S 26 B T.

Asc. 120 ft. over S. slope.

43.10 Spur, slopes SE., desc. 225 ft. over NE. slope.