

County Surveyor's Record, Douglas County, Oregon

Subdivision of T. 29 S., R. 3 E.

- CHAINS
8.00 Spur, slopes NE., desc. 85 ft. over NW. slope.
- 9.50 Foot of desc. on N. slope, asc., 115 ft. over NE. slope.
- 19.00 Spur, slopes N., desc. 75 ft. over NW. slope.
- 21.75 Spring branch, 5 lks. wide, course NE., asc. 350 ft. over broken NE. slope to
- 39.87 Set an iron post, 3 ft. long, 1 in. in diam., 30 ins. in the ground, for $\frac{1}{4}$ sec. cor. with brass cap marked

$$\begin{array}{r} S\ 24 \\ \frac{1}{4} S\ 25 \\ 1927 \end{array}$$

From Which.

A Pine, 8 ins. in diam., bears N.10*E., 26 lks., dist., marked $\frac{1}{4}$ S 24 B T.

A Fir, 8 ins. in diam., bears S.21*E., 55 lks., dist., marked $\frac{1}{4}$ S 25 B T.

Asc. 410 ft. over broken NE. slope.

- 56.00 Rocky spur, slopes S., asc. 10 ft. over broken S. slope.
- 63.85 Spur, slopes S., desc. 215 ft. over SW. slope.
- 75.75 Spring branch, 5 lks. wide, course S., asc. 115 ft. over SE. slope to
- 79.74 The cor. of secs. 23, 24, 25 & 26.

Land., Mountainous.

Soil., Sandy loam & rocky, 3rd rate.

Timber., Fir & pine.

Undergrowth., Huckleberry, small fir, pine and yew.

N.0*01'W., bet. secs. 23 & 24.

Over mountainous land, through heavy timber and medium undergrowth.

Asc. 110 ft. over S. slope.

- 12.60 Spur, slopes E., desc. 40 ft. over NE. slope.
- 15.02 Spring branch, 2 lks. wide, course E., asc. 375 ft. over S. slope to
- 40.00 Set an iron post, 3 ft. long, 1 in. in diam. 30 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked

$$\begin{array}{r} S\ 23\ S\ 24 \\ 1927 \end{array}$$