

## County Surveyor's Record, Douglas County, Oregon

Subdivision of T. 29 S., R. 3 E.

CHAINS	
	Desc. 225 ft. over NW. slope.
7.17	Creek, 10 lks. wide, course NE., asc. 155 ft. over SE. slope.
13.00	Spur, slopes NE., desc. 170 ft. over NW. slope.
18.30	Spring branch, 3 lks. wide, course NE., asc. 60 ft. over SE. slope.
24.40	Spur, slopes NE., desc. 160 ft. over NW. slope.
30.15	Creek, 18 lks. wide, course NE., asc. 130 ft. over SE. slope.
36.00	Spur, slopes E., desc. 75 ft. over NE. slope to
40.00	Set an iron post, 3 ft. long, 1 in. in diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked
	$\begin{array}{c} \frac{1}{4} \\ \text{S } 14 \text{   S } 13 \\ 1927 \end{array}$
	from which
	A Fir, 10 ins. in diam., bears S.25*E., 31 lks. dist., marked $\frac{1}{4}$ S 13 B T.
	A Fir, 30 ins. in diam., bears S.83*W., 73 lks. dist., marked $\frac{1}{4}$ S 14 B T.
	Desc. 5 ft. over NE. slope.
40.40	Foster Creek, 30 lks. wide, course E., asc. 350 ft. over S. slope.
60.70	Spur, slopes SW., desc. 85 ft. over NW. slope.
68.00	Draw, drains SW., asc. 140 ft. over S. slope to
80.00	Set an iron post, 3 ft. long, 2 ins. in diam., 30 ins. in the ground, for cor. of secs, 11,12,13 and 14., with brass cap marked
	$\begin{array}{c} \text{T } 29 \text{ S } \text{ R } 3 \text{ E} \\ \text{S } 11 \text{   S } 12 \\ \text{S } 14 \text{   S } 13 \\ 1927 \end{array}$
	from which
	A Fir, 28 ins. in diam., bears N.71 $\frac{1}{2}$ *E., 69 lks. dist., marked T 29 S R 3 E S 12 B T.
	A Pine, 14 ins. in diam., bears S.2*E., 60 lks. dist., marked T 29 S R 3 E S 13 B T.