

## County Surveyor's Record, Douglas County, Oregon

Subdivision of T. 29 S., R. 3 E.

CHAINS

A Fir, 18 ins. in diam., bears S.28\*W., 44 lks.,  
dist., marked T 29 S R 3 E S 14 B T.

A Fir, 15 ins. in diam., bears N.81\*W., 104 lks.,  
dist., marked T 29 S R 3 E S 11 B T.

Land., Mountainous.

Soil., Sandy loam, 2nd rate.

Timber., Fir, pine &amp; cedar.

Undergrowth., Small fir & pine, huckleberry, hazel and  
vine maple.

---

N.89\*53'E., on a random line, bet. secs. 12 & 13.

40.00 Set temp.  $\frac{1}{4}$  sec. cor.79.56 Intersect N. & S. line, 4 lks. N. of the cor. of secs.,  
7,12,13 & 18.

Thence

S.89\*55'W., on a true line.

Over mountainous land, through medium timber & medium  
undergrowth.

Desc. 220 ft. over SW. slope.

6.30 Spring branch, 1 lk. wide, course S., asc. 190 ft. over  
broken SE. slope to  $\frac{1}{4}$  sec. cor.

20.79 Spring branch, 2 lks. wide, course SE.

34.44 Spring branch, 3 lks. wide, course S.

39.78 Set an iron post, 3 ft. long, 1 in. in diam., 28 ins. in  
the ground, for  $\frac{1}{4}$  sec. cor., with brass cap marked
$$\begin{array}{r} S 12 \\ \frac{1}{4} S 13 \\ 1927 \end{array}$$

From which

A Fir, 28 ins. in diam., bears N.12\*E., 42 lks.,  
dist., marked  $\frac{1}{4}$  S 12 B T.

A Fir, 30 ins. in diam., bears S. 29\*W., 30 lks.  
dist., marked  $\frac{1}{4}$  S 13 B T.

Asc. 60 ft. over SE. slope.

44.60 Spur, slopes S., desc. 470 ft. over SW. slope to

79.56 The cor. of secs. 11,12,13 &amp; 14.