

County Surveyor's Record, Douglas County, Oregon

Subdivision of T. 29 S., R. 3 E.

CHAINS

Land., Mountainous.

Soil., Sandy loam & rocky, 3rd rate.

Timber., Fir, pine & cedar.

Undergrowth., Vine maple, huckleberry, small fir & pine.

N.0*01'W., bet. secs. 11 & 12.

Over mountainous land, through medium timber & dense undergrowth.

Asc. 545 ft. over SW. slope to $\frac{1}{4}$ sec. cor.

11.12 Spring branch, 1 lk. wide, course SW.

34.51 Spring branch, 1 lk. wide, course SW.

40.00 Set an iron post, 5 ft. long, 1 in. in diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor. with brass cap marked

$\frac{1}{4}$
 S 11 | S 12
 1927

From which

A Fir, 36 ins. in diam., bears S.62 $\frac{1}{2}$ *E., 114 lks., dist., marked $\frac{1}{4}$ S 12 B T

A Cedar, 60 ins. in diam., bears N.15*W., 12 lks., dist., marked $\frac{1}{4}$ S 11 B T.

Asc. 1100 ft. over broken SW. slope to sec. cor.

56.75 Forest Service Trail, bears E. & W., leave dense undergrowth.

80.00 Falls on N. edge of a level space, 3 x 3 ft. on a ledge, 20 ft. N. & S. 50 Ft. E. & W., and sloping W. at this point.

Cut a (x) for the cor. of secs. 1,2,11 & 12, with 1 groove E. & 5 grooves S. of the cross.,

From which

A Twin fir, 20 ins. in diam., bears N.55*E., 23 lks., dist., marked T 29 S R 3 E S 1 B T.

A Fir, 14 ins. in diam., bears S.34*E., 60 lks., dist., marked T 29 S R 3 E S 12 B T.

A Fir, 20 ins. in diam., bears S.83*W., 33 lks., dist., marked T 29 S R 3 E S 11 B T.