

Subdivision of T. 29 S., R. 3 E.

CHAINS

A Fir, 22 ins. in diam., bears N.17\*W., 173 lks.,  
dist., marked T 29 S R 3 E S 2 B T.

Build a mound of stone, 3 ft. base, 1½ ft. high, 5 ft.  
S. of the cor.

Land., Mountainous.

Soil., Sandy & rocky, 2nd & 4th rate.

Timber., Fir, pine & cedar.

Undergrowth., Small fir & pine, huckleberry, service and  
sage brush,

---

N.89\*55'E., on a random line bet. secs. 1 & 12.

40.00 Set temp. ¼ sec. cor.

79.84 Intersect N. & S. line, 20 lks. S. of the cor. of secs.  
1, 6, 7 & 12.

Thence

S.89\*46'W., on a true line.

Over mountainous land, through stunted timber and light  
undergrowth.

Desc. 160 ft. over NW. slope.

14.20 Spring branch, 1 lk. wide, course N., asc. 25 ft. over  
NE. slope.

19.00 Spur, slopes N., desc. 190 ft. over NW. slope.

36.00 Draw, drains N., asc. 20 ft. over NE. slope to

39.92 Set an iron post, 3 ft. long, 1 in. in diam., 30 ins. in  
the ground, for ¼ sec. cor., with brass cap marked

$$\frac{S \ 1}{\frac{1}{4} \ S \ 12}$$

1927

From which

A Pine, 12 ins. in diam., bears N.54\*E., 13 lks.,  
dist., marked ¼ S 1 B T.

A Fir, 36 ins. in diam., bears S.28\*E., 52 lks.,  
dist., marked ¼ S 12 B T.

Asc. 50 ft. over NE. slope.

43.00 Spur, slopes N., desc. 55 ft. over NW. slope.