

## County Surveyor's Record, Douglas County, Oregon

## Subdivision of T. 29 S., R. 3 E.,

CHAINS  
35.00

Enter medium undergrowth.

40.00

Spur, slopes E.

Set an iron post, 3 ft. long, 1 in. in diam., 28 ins. in  
the ground, for  $\frac{1}{4}$  sec. cor., with brass cap marked

$$\begin{array}{c} \frac{1}{4} \\ S\ 27\ | \ S\ 26 \\ 1927 \end{array}$$

From which

A Fir, 16 ins. in diam., bears N.8\*E., 163 lks.,  
dist., marked  $\frac{1}{4}$  S 26 B T.

A Fir, 10 ins. in diam., bears N.72 $\frac{1}{2}$ \*W., 69 lks.,  
dist., marked  $\frac{1}{4}$  S 27 B T.

Desc. 360 ft. over N. slope.

61.00

Spring branch, 5 lks. wide, course E., asc. 325 ft. over  
SE. slope to sec. cor.

65.82

Spring branch, 5 lks. wide, course SE.

76.00

Leave timber and undergrowth, bears NE. and SW., enter  
a grassy opening.

80.00

Set an iron post, 3 ft. long, 2 ins. in diam., 30 ins. in  
the ground, for cor. of secs. 22, 23, 26 & 27, with  
brass cap marked

$$\begin{array}{c} T\ 29\ S\ R\ 3\ E \\ S\ 22\ | \ S\ 23 \\ S\ 27\ | \ S\ 26 \\ 1927 \end{array}$$

from which

A Fir, 8 ins. in diam., bears N.18\*E., 416 lks.,  
dist., marked T 29 S R 3 E S 23 B T.

A Fir, 20 ins. in diam., bears S.39 $\frac{1}{2}$ \*E., 249 lks.,  
dist., marked T 29 S R 3 E S 26 B T.

A Cedar, 30 ins. in diam., bears S.39\*W., 274 lks.,  
dist., marked T 29 S R 3 E S 27 B T.

A Fir, 18 ins. in diam., bears N.2\*45'W., 350 lks.,  
dist., marked T 29 S R 3 E S 22 B T.

Land, mountainous.

Soil, sandy loam, 2nd rate.

Timber, fir, pine and cedar.

Undergrowth, huckleberry, vine maple, small fir and pine.