

County Surveyor's Record, Douglas County, Oregon

Subdivision of T. 29 S., R. 3 E.

CHAINS

N.0*02'W., bet. secs. 22 and 23.

Over rolling mountainous land, through grassy opening.

Over E. slope.

4.00 Spur, slopes SE., enter medium timber and medium undergrowth, bears E. and W.; desc 200 ft. over N. slope.

23.97 Creek, 6 lks. wide, course E.; asc. 20 ft. over SE. slope.

28.00 Spur, slopes E.; desc. 30 ft. over NE. slope.

35.95 Creek, 7 lks. wide, course SE.; asc. 25 ft. over S. slope to

40.00 Leave timber and undergrowth, enter grass land, bears NE. and NW.

Set an iron post, 3 ft. long, 1 in. in diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked
$$\begin{array}{c} \frac{1}{4} \\ \text{S } 22 \frac{1}{4} \text{ S } 23 \\ 1927 \end{array}$$

from which

A Fir, 12 ins. in diam., bears S.72*E., 163 lks. dist., marked $\frac{1}{4}$ S 23 B TA Cedar, 32 ins. in diam., bears N.81 $\frac{1}{2}$ *W., 252 lks. dist., marked $\frac{1}{4}$ S 22 B T.

Asc. 260 ft. over S. slope.

51.25 Spur, slopes SE., desc. 15 ft. over NE. slope.

55.00 Draw, course SE., asc. 200 ft. over S. slope.

69.00 Enter medium timber and dense undergrowth, bears E. and W.

69.90 Ridge, bears E. and W., desc. 190 ft. over NW. slope to

80.00 Set an iron post, 3 ft. long, 2 ins. in diam., 26 ins. in the ground, for cor. of secs. 14, 15, 22 and 23, with brass cap marked

$$\begin{array}{c} \text{T } 29 \text{ S } \text{ R } 3 \text{ E} \\ \text{S } 15 \text{ S } 14 \\ \text{S } 22 \text{ S } 23 \\ 1927 \end{array}$$

from which