

County Surveyor's Record, Douglas County, Oregon

Subdivision of T. 29 S., R. 3 E.

CHAINS
 56.89 Spring branch, 1 lk. wide, course E., asc. 160 ft. over SE. slope.
 73.50 Spur, slopes E., desc. 90 ft. over NE. slope to
 80.00 Set an iron post, 3 ft. long, 2 ins. in diam., 28 ins. in the ground, for cor. of secs. 2,3,10 and 11, with brass cap marked

T 29 S R 3 E
 S 3 S 2
 S 10 S 11
 1927

From which

A Fir, 16 ins. in diam., bears N.34 $\frac{1}{2}$ *E., 48 lks. dist., marked T 29 S R 3 E S 2 B T.
 A Fir, 20 ins. in diam., bears S.66 $\frac{1}{8}$ *E., 59 lks. dist., marked T 29 S R 3 E S 11 B T.
 A Fir, 16 ins. in diam., bears S.50*W., 49 lks. dist., marked T 29 S R 3 E S 10 B T.
 A Fir, 15 ins. in diam., bears N.45*W., 45 lks. dist., marked T 29 S R 3 E S 3 B T.

Land, Mountainous.

Soil, Sandy & gravelly loam, 2nd rate.

Timber, Fir, pine, hemlock and larch.

Undergrowth, Huckleberry, vine maple, small fir, hemlock and pine.

N.89*56'E., on a random line bet. secs. 2 and 11.
 40.00 Set temp. $\frac{1}{4}$ sec. cor.
 30.22 Intersect N. & S. line 16 lks. N. of the cor. of secs, 1,2,11 and 12.
 Thence
 N.89*57'W., on a true line.
 Over mountainous land, through scattering timber and open grassy land.
 Desc. 1020 ft. over SW. slope to
 40.11 Set an iron post, 3 ft. long, 1 in. in diam., 32 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked