

County Surveyor's Record, Douglas County, Oregon

Subdivision of T. 29 S., R. 3 E.

CHAINS	N.0*02'W., bet. secs. 27 and 28.
	Over rolling mountainous land, through scattering timber and light undergrowth.
	Desc. 30 ft. over NW. slope.
3.50	Spring branch, 3 lks. wide, course W., thence over W. slope.
12.60	Flat Creek, 12 lks. wide, course S.5*W., asc. 255 ft. over SE. slope.
36.45	Forest Service Trail, and top of a ridge, bears NE. and SW., thence over W. slope to
40.00	Set an iron post, 3 ft. long, 1 in. in diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked
	$\begin{array}{c} \frac{1}{4} \\ S\ 28\ \big \ S\ 27 \\ 1927 \end{array}$
	from which
	A Fir, 34 ins. in diam., bears S.69*E., 43 lks. dist., marked $\frac{1}{2}$ S 27 B T.
	A Fir, 12 ins. in diam., bears S.74*W., 28 lks. dist., marked $\frac{1}{2}$ S 28 B T.
	Asc. 255 ft. over SW. slope.
75.00	Spur, slopes W., desc, 85 ft. over NW. slope to
80.00	Falls on N. face, of nearly perpendicular ledge, 15 ft. high, 40 ft. E. and W., at this point.
	Cut a cross (x) for the cor. of secs. 21, 22, 27 and 28, with 2 grooves S. and 3 grooves E. of the cross.;
	from which
	A Hemlock, 28 ins. in diam., bears N.20*E., 64 lks. dist., marked T 29 S R 3 E S 22 B T.
	A Hemlock, 12 ins. in diam., bears S.36*E., 48 lks. dist., marked T 29 S R 3 E S 27 B T.
	A Hemlock, 12 ins. in diam., bears S.24*W., 15 lks. dist., marked T 29 S R 3 E S 28 B T.
	A Fir, 48 ins. in diam., bears N.1*W., 148 lks. dist., marked T 29 S R 3 E S 21 B T.
	Land, rolling mountainous.
	Soil, gravelly and rocky, 2nd rate.