

County Surveyor's Record, Douglas County, Oregon

Subdivision of T. 29 S., R. 3 E.

CHAINS

A Larch, 24 ins. in diam., bears S.10*E., 154 lks.
dist., marked $\frac{1}{2}$ S 10 B T.

A Fir, 20 ins. in diam., bears N.6*W., 232 lks.
dist., marked $\frac{1}{2}$ S 9 B T.

Desc. 145 ft. over NE. slope.

66.03 Spring branch, 1 lk. wide, course E.; asc. 60 ft. over
SE. slope.

76.00 Top of asc. on E. slope, desc. 10 ft. along E. slope to

80.00 Set an iron post, 3 ft. long, 2 ins. in diam., 12 ins. in
the ground, to bed rock, in a mound of stone, 4 ft.
base, $1\frac{1}{2}$ ft. high, for cor. of secs. 3,4,9 and 10, with
brass cap marked

T 29 S R 3 E
S 4 | S 3
S 9 | S 10
1927

from which

A Fir, 30 ins. in diam., bears N.44*E., 123 lks.
dist., marked T 29 S R 3 E S 3 B T.

A Fir, 28 ins. in diam., bears S.27*E., 92 lks.
dist., marked T 29 S R 3 E S 10 B T.

A Larch, 22 ins. in diam., bears S.74*W., 66 lks.
dist., marked T 29 S R 3 E S 9 B T.

A Fir, 22 ins. in diam., bears N.20 $\frac{1}{2}$ *W., 41 lks.
dist., marked T 29 S R 3 E S 4 B T.

Land, mountainous.

Soil, gravelly, 3rd rate.

Timber, Fir, pine, cedar and larch.

Undergrowth, huckleberry, service, small fir and larch.

S.89*52'E., on a random line bet. secs. 3 and 10.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

80.20 Intersect N. and S. line 26 lks. S. of the cor. of secs.
2,3,10 and 11.

Thence

S.89*57'W., on a true line.

Over mountainous land, through medium timber and medium