

County Surveyor's Record, Douglas County, Oregon

Subdivision of T. 29 S., R. 3 E.

|        |   |
|--------|---|
| CHAINS | <p>cross, bears N.40*E., 24 lks. dist.<br/> Asc. 40 ft. over SW. slope.</p> <p>40.00 True point for <math>\frac{1}{4}</math> sec. cor., falls on steep face of rock, where it is impractical to set a corner.</p> <p>40.40 Top of a rock point, projecting W., desc 780 ft. over NW. slope.</p> <p>59.21 Spring branch, 6 lks. wide, course NW., continue desc.</p> <p>70.10 Draw, drains W., asc. 225 ft. over SW. slope.</p> <p>77.40 Rocky spur, slopes W., desc. 70 ft. over N. slope to</p> <p>80.00 Set an iron post, 3 ft. long, 2 ins. in diam., 28 ins. in the ground, for the cor. of secs. 28,29,32 and 33, with brass cap marked</p> <div style="text-align: center;"> <p>T 29 S R 3 E.<br/> S 29   S 28<br/> S 32   S 33<br/> 1927</p> </div> <p>from which</p> <p>A Fir, 16 ins. in diam., bears N.12*E., 84 lks. dist., marked T 29 S R 3 E S 28 B T.</p> <p>A Fir, 9 ins. in diam., bears S.8*E., 29 lks. dist., marked T 29 S R 3 E S 33 B T.</p> <p>A Fir, 12 ins. in diam., bears S.55*W., 15 lks. dist., marked T 29 S R 3 E S 32 B T.</p> <p>A Fir, 12 ins. in diam., bears N.28*W., 120 lks. dist., marked T 29 S R 3 E S 29 B T.</p> <p>Land, mountainous.<br/> Soil, sandy and rocky. 3rd rate.<br/> Timber, fir and pine, much of which is fire killed.<br/> Undergrowth, huckleberry, blackberry, small fir and pine.</p> <hr/> <p>East, on a random line bet. secs. 28 and 33.</p> <p>40.00 Set temp. <math>\frac{1}{4}</math> sec. cor.</p> <p>80.38 Intersect N. and S. line 30 lks. S. of the cor. of secs. 27,28,33 and 34.</p> <p>Thence<br/> S.89*47'W., on a true line.<br/> Over mountainous land, through medium timber and medium undergrowth.</p> |
|--------|---|