

County Surveyor's Record, Douglas County, Oregon

Subdivision of T. 29 S. R. 3 E.

CHAINS	
	SW. slope to
40.00	Set an iron post 3 ft. long, 1 in. in diam., 30 ins. in
	the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked
	$\begin{array}{c} \frac{1}{4} \\ S\ 29\   \ S\ 28 \\ 1927 \end{array}$
	from which
	A Fir, 40 ins. in diam., bears S.15*E., 20 lks.
	dist., marked $\frac{1}{4}$ S 28 B T.
	A Fir, 10 ins. in diam., bears N.57*W., 50 lks.
	dist., marked $\frac{1}{4}$ S 29 B T.
	Asc. 5 ft. over SW. slope.
43.00	Top of bank, bears E. and W., desc. 50 ft. over N. slope.
46.56	Spring branch, 3 lks. wide, course NW., thence over W.
	slope.
50.00	Spring branch, 5 lks. wide, course W., asc. 80 ft. over
	S. slope.
57.00	Spur, slopes SW., leave thicket, bears NE. and SW., desc.
	55 ft. over NW. slope.
65.25	Lone Woman Creek, 20 lks. wide, course SW., asc. 205 ft.
	over SE. slope.
77.00	Spur, slopes SW., thence over W. slope to
80.00	Set an iron post, 3 ft. long, 2 ins. in diam., 28 ins. in
	the ground, for cor. of secs. 20,21,28 and 29, with
	brass cap marked
	$\begin{array}{c} T\ 29\ S\ R\ 3\ E \\ S\ 20\   \ S\ 21 \\ S\ 29\   \ S\ 28 \\ 1927 \end{array}$
	from which
	A Hemlock, 28 ins. in diam., bears N.85*E., 35 lks.
	dist., marked T 29 S R 3 E S 21 B T.
	A Hemlock, 12 ins. in diam., bears S.20*E., 18 lks.
	dist., marked T 29 S R 3 E S 28 B T.
	A Fir, 14 ins. in diam., bears S.69*W., 32 lks.
	dist., marked T 29 S R 3 E S 29 B T.
	A Hemlock, 18 ins. in diam., bears N.5*W., 19 lks.
	dist., marked T 29 S R 3 E S 20, B T.