

County Surveyor's Record, Douglas County, Oregon

Subdivision of T. 29 S.; R. 3 E.

CHAINS	
58.00	Spur, slopes S., desc. 200 ft. over broken SW. slope to sec, cor.
80.42	The cor. of secs. 16,17,20 and 21. Land, mountainous. Soil, sandy and rocky, 3rd rate. Timber, fir, cedar, pine and hemlock. Undergrowth, huckleberry and vine maple,
	N.0*03'W., bet. secs. 16 and 17. Over mountainous land, through medium timber, and medium undergrowth. Asc. 285 ft. over rocky S. slope.
7.40	Spur, slopes SW., asc. 10 ft. over W. slope.
10.90	Draw, drains SW., asc. 430 ft. over S. slope.
25.50	Ridge, bears E. and W., desc. 360 ft. over broken NE. slope to
40.00	Set an iron post, 3 ft. long, 1 in. in diam., 34 ins. in the ground, for $\frac{1}{4}$ sec. cor. with brass cap marked <div style="text-align: center;"> $\begin{array}{c} \frac{1}{4} \\ S\ 17\ \ S\ 16 \\ 1927 \end{array}$ </div> from which A Larch, 14 ins. in diam., bears N.70*E., 42 lks. dist., marked $\frac{1}{4}$ S 16 B T. A Fir, 26 ins. in diam., bears S.82*W., 13 lks. dist., marked $\frac{1}{4}$ S 17 B T. Desc. 665 ft. over broken NE. slope to
80.00	Set an iron post, 3 ft. long, 2 ins. in diam., 20 ins. in the ground, to rock in a mound of stone, 2 $\frac{1}{2}$ ft. base, 1 ft. high, for cor. of secs. 8,9,16 and 17, with brass cap marked <div style="text-align: center;"> $\begin{array}{c} T\ 29\ S\ R\ 3\ E \\ S\ 8\ \ S\ 9 \\ S\ 17\ \ S\ 16 \\ 1927 \end{array}$ </div> from which A Fir, 22 ins. in diam., bears N.8*E., 60 lks. dist., marked T 29 S R 3 E S 9 B T.