

County Surveyor's Record, Douglas County, Oregon

Subdivision of T. 29 S., R. 3 E.

CHAINS

A Fir, 24 ins. in diam., bears S.64*E., 51 lks.
dist., marked T 29 S R 3 E S 16 B T.

A Fir, 24 ins. in diam., bears S.63*W., 24 lks.
dist., marked T 29 S R 3 E S 17 B T.

A Pine, 22 ins. in diam., bears N.52*W., 19 lks.
dist., marked T 29 S R 3 E S 8 B T.

Land, mountainous.

Soil, sandy and rocky, 3rd rate.

Timber, fir, cedar, pine and larch.

Undergrowth, huckleberry, vine maple, small fir, pine and
yew.

N.89*53'E., on a random line bet. secs. 9 and 16.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

80.04 Intersect N. and S. line 13 lks. S. of the cor. of secs.
9, 10, 15 and 16.

Thence

S.89*47'W., on a true line.

Over rolling mountainous land, through patches of heavy
timber, light undergrowth, and grassy openings.

Desc. 430 ft. over SW. slope.

20.85 Spring branch, 2 lks. wide, course NW., desc. 190 ft.
over NW. slope to $\frac{1}{4}$ sec. cor.

23.95 Spring branch, 2 lks. wide, course NW.

40.02 Set an iron post, 3 ft. long, 1 in. in diam., 28 ins. in
the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked

$$\begin{array}{r} \frac{1}{4} \text{ S } 9 \\ \text{S } 16 \\ 1927 \end{array}$$

from which

A Fir, 20 ins. in diam., bears N.28*E., 34 lks.
dist., marked $\frac{1}{4}$ S 9 B T.

A Fir, 42 ins. in diam., bears S.0*30'W., 35 lks.
dist., marked $\frac{1}{4}$ S 16 B T.

Desc. 15 ft. over NW. slope.

42.00 Draw, drains NW., asc. 30 ft. over NE. slope.