

County Surveyor's Record, Douglas County, Oregon

Subdivision of T. 29 S., R. 3 E.

CHAINS

- 18.00 Lone Woman Creek, 20 lks. wide, course W., asc. 75 ft. over S. slope to, enter old burn, bears NE. and SW.,
- 20.00 Low spur, slopes SW., thence over rough land, sloping slightly to the West.
- 30.37 Spring branch, 6 lks. wide, course, W., asc. 200 ft. over rocky broken SW. slope to,  $\frac{1}{4}$  sec. cor.
- 35.50 Rock spur, slopes SW.
- 40.00 Set an iron post, 3 ft. long, 1 in. in diam., 30 ins. in the ground, in a small mound of stone, for  $\frac{1}{4}$  sec. cor., with brass cap marked

$\frac{1}{4}$   
 S 30 | S 29  
 1927

from which ( No live trees available )

A Dead Fir, 20 ins, in diam., bears S.30\*E., 12 lks. dist., marked  $\frac{1}{4}$  S 29 B T.

A Dead Cedar, 11 ins. in diam., bears N.60\*W., 39 lks. dist., marked  $\frac{1}{4}$  S 30 B T.

Asc. 220 ft. over broken SW. slope.

- 46.50 Enter medium heavy green timber, bears E. and W.
- 56.00 Spur, slopes W., desc. 10 ft. over W. slope.
- 58.00 Spring branch, 2 lks. wide, course SW., asc. 315 ft. over SE. slope to
- 80.00 Set an iron post, 3 ft. long, 2 ins. in diam., 30 ins. in the ground, for cor. of secs. 19,20,29 and 30, with brass cap marked

T 29 S R 3 E  
 S 19 | S 20  
 S 30 | S 29  
 1927

from which

A Cedar, 12 ins. in diam., bears N.43\*E., 38 lks. dist., marked T 29 S R 3 E S 20 B T.

A Fir, 36 ins. in diam., bears S.44\*E., 62 lks. dist., marked T 29 S R 3 E S 29 B T.

A Fir, 7 ins. in diam., bears S.39\*W., 36 lks. dist., marked T 29 S R 3 E S 30 B T.

A Cedar, 16 ins. in diam., bears N.87\*W., 94 lks. dist., marked T 29 S R 3 E S 19 B T.