

County Surveyor's Record, Douglas County, Oregon

Subdivision of T. 29 S., R. 3 E.

CHAINS

Land, mountainous.  
Soil, sandy and gravelly, 3rd rate.  
Timber, fir, pine and cedar.  
Undergrowth, vine maple, small fir, pine and hemlock.

N.0\*04'W., bet secs. 19 and 20.

Over mountainous land, through medium timber and medium undergrowth.

Asc. 410 ft. over SW. slope.

- 7.65 Forest Service Trail, bears NE. and SW.
- 15.30 Spring branch, 3 lks. wide, course SW., continue asc.
- 36.30 Spur, slopes SW., desc. 45 ft. over NW. slope to
- 40.00 Set an iron post, 3 ft. long, 1 in. in diam., 30 ins. in  
. the ground, for  $\frac{1}{4}$  sec. cor., with brass cap marked

S 19 <sup>$\frac{1}{4}$</sup>  S 20  
1927

from which

A Fir, 30 ins. in diam., bears S.78\*E., 30 lks.  
dist., marked  $\frac{1}{4}$  S 20 B T.

A Fir, 42 ins. in diam., bears S.87 $\frac{1}{2}$ \*W., 84 lks.  
dist., marked  $\frac{1}{2}$  S 19 B T.

Desc. 250 ft. over NW. slope.

- 60.01 Spring branch, 3 lks. wide, course W., asc. 40 ft. over  
SW. slope.
- 63.50 Spur, slopes W., desc. 75 ft. over NW. slope.
- 67.70 Draw, drains W., asc. 190 ft. over SW. slope.
- 79.50 Spur, slopes W., desc. slightly over NW. slope to
- 80.00 Set an iron post, 3 ft. long, 2 ins. in diam., 30 ins. in  
the ground, for cor. of secs. 17,18,19and 20, with  
brass cap marked

T 29 S R 3 E  
S 18 | S 17  
S 19 | S 20  
1927

from which

A Hemlock, 16 ins. in diam., bears N.88 $\frac{1}{2}$ \*E., 76 lks.  
dist., marked T 29 S R 3 E S 17 B T.