

Subdivision of T. 29 S., R. 3 E.

CHAINS

70.10

Ridge, bears E and W; desc. 195 ft. over NE slope to

80.00

Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, for the corner of Secs. 7, 8, 17 and 18, with brass cap marked

T 29	S	R	3	E
S	7	S	8	
S	18	S	17	
			1927	

from which

A Fir, 24 ins. diam., bears N.39*E., 34½ lks. dist., marked T 29 S R 3 E S 8 B T.

A Fir, 22 ins. diam., bears S.10*E., 52 lks. dist., marked T 29 S R 3 E S 17 B T.

A Larch, 18 ins. diam., bears S.73*W., 50 lks. dist., marked T 29 S R 3 E S 18 B T.

A Fir, 10 ins. diam., bears N.31*W., 42½ lks. dist., marked T 29 S R 3 E S 7 B T.

Land, mountainous.

Soil, sandy and rocky; 3rd rate.

Timber, Fir, Pine, Cedar and Larch.

Undergrowth, Vinemaple, Huckleberry, small Fir, Pine and Cedar.

N.89*41'E., on a random line bet. Secs. 8 and 17.

40.00

Set temp. ¼ Sec. corner.

80.38

Intersect N and S line 44 lks. N of the corner of Secs. 8, 9, 16 and 17.

Thence

West, on a true line.

Over mountains land, through stunted timber and light undergrowth.

Ascend 600 ft. over broken rocky NE slope.

22.30

Spur, slopes N; descend 105 ft. over NW slope.

31.60

Draw, drains N; ascend 195 ft. over NE slope.

38.50

Spur, slopes N; descend 25 ft. over NW slope to

40.19

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, for ¼ Sec. corner, with brass cap marked