

County Surveyor's Record, Douglas County, Oregon

Subdivision of T. 29 S., R. 3 E.

CHAINS 48.42	Spring branch, 2 lks. wide, course NE., asc. 10 ft. over SE. slope.
52.00	Top of asc. on E. slope; desc. 380 ft. over NE. slope.
68.80	Spring branch, 1 lk. wide, course NW., asc. 60 ft. over SW. slope.
73.75	Spur, slopes NW., desc. 270 ft. over N. slope to
80.00	Set an iron post, 3 ft. long, 2 ins. in diam., 28 ins. in the ground, for cor. of secs. 5,6,7, and 8, with brass cap marked
	T 29 S R 3 E S 6 S 5 S 7 S 8 1927
	from which
	A Fir, 30 ins. in diam., bears N.33 $\frac{1}{2}$ *E., 138 lks. dist., marked T 29 S R 3 E S 5 B T.
	A Fir, 36 ins. in diam., bears S.51 $\frac{1}{2}$ *E., 86 lks. dist., marked T 29 S R 3 E S 8 B T.
	A Fir, 32 ins. in diam., bears S.13 $\frac{1}{2}$ *W., 45 lks. dist., marked T 29 S R 3 E S 7 B T.
	A Fir, 40 ins. in diam., bears N.38*W., 25 lks. dist., marked T. 29 S R 3 E S 6 B T.
	Land, mountainous.
	Soil, sandy and rocky, 3rd rate,
	Timber, fir, pine, hemlock and cedar.
	Undergrowth, vine maple, huckleberry, small fir, pine and hemlock.
	East, on a random line bet. secs. 5 and 8
40.00	Set temp. $\frac{1}{4}$ sec. cor.
80.44	Intersect N. and S. line 23 lks. S. of the cor. of secs. 4,5,8 and 9.
	Thence
	S,89*50*W., on a true line.
	Over mountainous land, through medium timber and medium undergrowth.
	Desc. 600 ft. over broken W. slope.