

County Surveyor's Record, Douglas County, Oregon

East and North Boundaries and Subdivisions of T. 29 S., R. 4 E., as surveyed by Herbert N. Raymond, U.S.C.E., under Special Instructions, dated March 22, 1930.

CHAINS

East Boundary.

From the cor. of Ts. 29 and 30 S., Rs. 4 and 5 E., which is an iron post, 3 ins. diam., 8 ins. above ground, with brass cap mkd. and witnessed as described in the field notes of T. 30 S., R. 4 E.


North, bet. secs. 31 and 36.

Asc. 20 ft. over S. slope, through heavy timber and light undergrowth.

2.00 A low spur, bears SW.; desc. 50 ft. over NW. slope.

24.00 Draw, drains SW.; asc. 135 ft. over S. slope to

40.00 Set an iron post, 3 ft. long, 1 in. diam., 14 ins. in the ground, to rock, and build a mound of stone, 4 ft. base, 1 ft. high around the post, for 1/4 sec. cor. with brass cap mkd.



from which

A fir, 16 ins. diam., bears S. 89\* E., 25 lks. dist., mkd. 1/4 S 31 B T.

A fir, 16 ins. diam., bears S. 42\* W., 7 lks. dist., mkd., 1/4 S 36 B T.

Asc. 10 ft. over S. slope.

44.00 Spur, bears SW.; desc. 85 ft. over NW. slope.

55.37 Creek, 4 lks. wide, course SW.; asc. 100 ft. over S. slope to sec. cor.

73.90 A dim trail, bears E. and W.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in