

County Surveyor's Record, Douglas County, Oregon

Township 29 South, Range 4 East.

East Boundary.

CHAINS

the ground, for cor. of secs. 25, 30, 31, and 36, with
brass cap mkd.

T 29 S
R 4 E R 5 E
S 25 S 30
S 36 S 31
1930

from which

A fir, 22 ins. diam., bears N. 68* E., 51 lks.
dist., mkd. T 29 S R 5 E S 30 B T.

A fir, 24 ins. diam., bears S. 18* E., 20 lks.
dist., mkd. T 29 S R 5 E S 31 B T.

A fir, 20 ins. diam., bears S. 44* W., 37 lks.
dist., mkd. T 29 S R 4 E S 36 B T.

A fir, 18 ins. diam., bears N. 54* W., 79 lks.
dist., mkd. T 29 S R 4 E S 25 B T.

Land, rolling mountainous.

Soil, sandy loam and rocky. 2nd to 4th rate.

Timber, fir, hemlock and cedar.

Undergrowth, small fir and hemlock.

North, bet. secs. 25 and 30.

Asc. 80 ft. over S. slope, through medium timber and
light undergrowth.

14.00 Top of asc. on W. slope. thence over W. slope.

20.00 Desc. 515 ft. over NW. slope to $\frac{1}{4}$ sec. cor.

39.00 Enter an alder thicket, bears NE. and SW.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in
the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$
S 25 S 30
1930

from which