

County Surveyor's Record, Douglas County, Oregon

Township 29 South, Range 4 East.

East Boundary.

CHAINS

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, for cor. of secs. 7, 12, 13 and 18, with brass cap mkd.

T 29 S
R 4 E R 5 E
S 12 S 7
S 13 S 18
1930

from which

A fir, 18 ins. diam., bears N. 39 $\frac{1}{2}$ * E., 47 lks. dist., mkd. T 29 S R 5 E S 7 B T.

A fir, 12 ins. diam., bears S. 22* E., 11 lks. dist., mkd. T 29 S R 5 E S 18 B T.

A fir, 16 ins. diam., bears S. 27* W., 16 lks. dist., mkd. T 29 S R 4 E S 13 B T.

A fir, 8 ins. diam., bears N. 66 $\frac{1}{2}$ * W., 88 lks. dist., mkd. T 29 S R 4 E S 12 B T.

Land, mountainous and rolling.

Soil, sandy loam and rocky, 2nd to 4th rate.

Timber, fir, pine, and cedar.

Undergrowth, small fir, pine, and hemlock.

North, bet. secs. 7 and 12.

Asc. 180 ft. over SW. slope, through medium timber and dense undergrowth to

40.00 Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$
S 12 S 7
1930

, from which

A fir, 24 ins. diam., bears S. 22* E., 34 lks. dist., mkd. $\frac{1}{4}$ S 7 B T.