

# County Surveyor's Record, Douglas County, Oregon

10881/

Township 29 South, Range 4 East.

North Boundary.

CHAINS

N. 89°59' E., on a true line, bet. secs. 5 and 32.

Asc. 415 ft. over broken NW. slope, through stunted timber and dense undergrowth.

38.00 Spur, bears N.; desc. 10 ft. over NE. slope to

40.00 Set an iron post, 3 ft. long, 1 in. diam., 24 ins. in the ground, to rock, and build a mound of stone, 3 ft. base, 1 ft. high, around the post, for  $\frac{1}{4}$  sec. cor. with brass cap mkd.

$$\begin{array}{r} \frac{1}{4} \text{ S } 32 \\ \text{S } 5 \\ \hline 1930 \end{array}$$

from which

A fir, 20 ins. diam., bears S. 86° E., 25 lks. dist., mkd.  $\frac{1}{4}$  S 5 B T.

A fir, 6 ins. diam., bears N. 67 $\frac{1}{2}$ ° W., 38 lks. dist., mkd.  $\frac{1}{4}$  S 32 B T.

Desc. 105 ft. over NE. slope.

51.70 Draw, drains N.; asc. 110 ft. over NW. slope.

64.10 Spur, bears NE.; desc. 75 ft. over SE. slope.

68.00 Draw, drains S.; asc. 275 ft. over W. slope.

78.50 Top of a rock peak; desc. 25 ft. over SE. slope to

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 12 ins. in the ground, to rock, and build a mound of stone, 4 ft. base, 2 ft. high, around the post, for cor. of secs. 4, 5, 32, and 33, with brass cap mkd.

$$\begin{array}{r} \text{T } 28 \text{ S } \text{R } 4 \text{ E} \\ \text{S } 32 \text{ | } \text{S } 33 \\ \hline \text{S } 5 \text{ | } \text{S } 4 \\ \text{T } 29 \text{ S} \\ \hline 1930 \end{array}$$

from which

A fir, 5 ins. diam., bears N. 82° W., 83 lks. dist., mkd. T 28 S R 4 E S 32 B T

No other trees available.

Land, mountainous.