

County Surveyor's Record, Douglas County, Oregon

Township 29 South, Range 4 East.

North Boundary.

CHAINS

Soil, sandy loam and rocky, 2nd to 4th rate.
 Timber, fir, hemlock, cedar, and pine.
 Undergrowth, mountain laurel, small fir, hemlock, and
 pine.

N. 89*59' E., on a true line bet. secs. 4 and 33.
 Desc. 535 ft. over E. slope, through scattering stunted
 timber and very dense undergrowth.

- 21.00 Enter heavy timber, bears N. and S.
- 25.00 Draw, drains SE.; asc. 90 ft. over SW. slope.
- 34.00 Spur, bears S.; desc. 125 ft. over SE. slope to
- 40.00 Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in
 the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$ $\frac{S\ 33}{S\ 4}$
 1930

from which

- A fir, 12 ins. diam., bears N. 84* E., 113 lks.
 dist., mkd. $\frac{1}{4}$ S 33 B T.
- A fir, 36 ins. diam., bears S. 22* E., 51 lks.
 dist., mkd. $\frac{1}{4}$ S 4 B T.

Desc. 710 ft. over SE. and E. slopes.

- 66.20 Trail, bears N. and S.
- 67.40 Creek, 10 lks. wide, course S.; thence over S. slope.
- 71.60 Asc. 65 ft. over W. slope.
- 73.17 Trail, bears N. and S.
- 75.00 Top of asc.; thence over nearly level land.
- 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in
 the ground, for cor. of secs. 3, 4, 33, and 34, with
 brass cap mkd.

T 28 S R 4 E
 S 33 | S 34
 S 4 | S 3
 T 29 S
 1930