

County Surveyor's Record, Douglas County, Oregon

Township 29 South, Range 4 East.

North Boundary.

CHAINS

58.00 Top of asc.; thence over rolling land to
 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in
 the ground, for cor. of secs. 2, 3, 34, and 35, with
 brass cap mkd.

T 28 S R 4 E
S 34 S 35
S 3 S 2
T 29 S
1930

from which

A fir, 12 ins. diam., bears N. 35* E., 30 lks.
 dist., mkd. T 28 S R 4 E S 35 B T.

A fir, 14 ins. diam., bears S. 35* E., 70 lks.
 dist., mkd. T 29 S R 4 E S 2 B T.

A fir, 10 ins. diam., bears S. 80* W., 14 lks.
 dist., mkd. T 29 S R 4 E S 3 B T.

A fir, 20 ins. diam., bears N. 20* W., 68 lks.
 dist., mkd. T 28 S R 4 E S 34 B T.

Land, rolling.

Soil, sandy loam, 2nd rate.

Timber, fir, pine, and hemlock.

Undergrowth, alder, small fir, pine, and hemlock.

N. 89*59' E., on a true line bet. secs. 2 and 35.

Asc. 15 ft. over rolling SW. slope, through heavy timber
 and light undergrowth.

28.40 Desc. 175 ft. over SE. slope.

34.00 Rogue River, 40 lks. wide, course S.; asc. 60 ft. over
 W. slope to

40.00 Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in
 the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

S 35
$\frac{1}{4}$ S 2
1930

from which