

County Surveyor's Record, Douglas County, Oregon

Township 29 South, Range 4 East.

North Boundary.

CHAINS

A fir, 18 ins. diam., bears S. 28* W., 52 lks.,
dist., mkd. $\frac{1}{4}$ S 2 B T.

A fir, 10 ins. diam., bears N. 13* W., 67 lks.
dist., mkd. $\frac{1}{4}$ S 35 B T.

Asc. 210 ft. over NW. slope to

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 32 ins. in
the ground, for cor. of secs. 1, 2, 35, and 36, with
brass cap mkd.

T 28 S	R 4 E
S 35	S 36
S 2	S 1
T 29 S	
1930	

from which

A fir, 24 ins. diam., bears N. 20* E., 38 lks.
dist., mkd. T 28 S R 4 E S 36 B T.

A pine, 14 ins. diam., bears S. 42* E., 44 lks.
dist., mkd. T 29 S R 4 E S 1 B T.

A pine, 20 ins. diam., bears S. 51* W., 54 lks.
dist., mkd. T 29 S R 4 E S 2 B T.

A pine, 18 ins. diam., bears N. 82* W., 32 lks.
dist., mkd. T 28 S R 4 E S 35 B T.

Land, rolling and rolling mountainous.

Soil, sandy loam, 2nd rate.

Timber, fir, pine, and hemlock.

Undergrowth, small fir, pine, and hemlock.

N. 89*59' E., on a true line bet. secs. 1 and 36.

Asc. 140 ft. over SW. slope to $\frac{1}{4}$ sec. cor., through
heavy timber and light undergrowth.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in
the ground, for $\frac{1}{4}$ sec. cor., with brass cap. mkd.

$\frac{1}{4}$ S 36
S 1
1930

from which