

# County Surveyor's Record, Douglas County, Oregon

Township 29 South, Range 4 East.

North Boundary.

CHAINS

A Pine, 22 ins. diam., bears N. 6\* E., 32 lks.  
dist., mkd. 1/4 S 36 B T.

A fir, 14 ins. diam., bears S. 41\* W., 32 lks.  
dist., mkd. 1/4 S 1 B T.

Asc. 160 ft. over SW. slope.

52.70 Diamond Lake Road, bears SW. and NE.

69.50 Diamond Lake Road, bears NW. and SE.

73.20 Diamond Lake Road, bears SW. and NE.; desc. 30 ft. over  
SE. slope.

77.50 Gully, drains SW.; asc. 40 ft. over NW. slope to

80.00 The cor. of Ts. 28 and 29 S., Rs. 4 and 5 E.

Land, rolling.

Soil, sandy loam, 2nd rate.

Timber, fir, hemlock, pine, and larch.

Undergrowth, small fir, pine, and hemlock.

---

### Subdivision.

---

From the cor. of secs. 1, 2, 35, and 36, on S. bdy. of  
township, which is an iron post, 2 ins. diam., 16 ins.  
above ground, in a mound of stone, with brass cap mkd.  
and witnessed as described in the field notes of T.  
30 S., R. 4 E.

N. 0\*01' W., bet. secs. 35 and 36.

Asc. 35 ft. over S. slope, through medium timber and  
medium undergrowth.

19.80 A trail and top (OS) asc., bears NE. and SW.; desc. 15 ft.  
over NW. slope to

40.00 Set an iron post, 3 ft. long, 1 in. diam., 29 ins. in  
the ground, for 1/4 sec. cor., with brass cap mkd.