

## County Surveyor's Record, Douglas County, Oregon

Township 29 South, Range 4 East.

Subdivision.

CHAINS

N. 0°01' W., bet. secs. 23 and 24.

Desc. 90 ft. over NW. slope, through medium timber and medium undergrowth.

17.80 Foot of desc.; thence over rolling W. slope to

40.00 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.
$$\begin{array}{c} \frac{1}{4} \\ \text{S } 23 \mid \text{S } 24 \\ 1930 \end{array}$$

from which

A fir, 8 ins. diam., bears N. 63° E., 15 lks. dist., mkd.  $\frac{1}{4}$  S 24 B T.A fir, 10 ins. diam., bears S. 53° W., 46 lks. dist., mkd.  $\frac{1}{4}$  S 23 B T.

Desc. 285 ft. over NW. slope.

57.05 National Creek, 20 lks. wide, course SW.; asc. 170 ft. over S. slope.

59.70 Trail, bears NE. and SW.

71.00 Spur, bears SW.; desc. 100 ft. over NW. slope.

74.20 Trail, bears NE. and SW.

75.15 Creek, 5 lks. wide, course SW.; asc. 85 ft. over S. slope.

76.00 Trail, bears NW. and SE.

77.00 Top of asc.; thence over nearly level land to

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, for cor. of secs. 13, 14, 23, and 24, with brass cap mkd.

$$\begin{array}{c} \text{T } 29 \text{ S } \mid \text{R } 4 \text{ E} \\ \text{S } 14 \mid \text{S } 13 \\ \hline \text{S } 23 \mid \text{S } 24 \\ 1930 \end{array}$$

from which

A pine, 26 ins. diam., bears N. 40 $\frac{1}{2}$ ° E., 62 lks. dist., mkd. T 29 S R 4 E S 13 B T.