

County Surveyor's Record, Douglas County, Oregon

Township 29 South, Range 4 East.

Subdivision.

CHAINS	
	<p>A fir, 16 ins. diam., bears S. 10* E., 42 lks. dist., mkd. T 29 S R 4 E S 24 B T.</p> <p>A pine, 24 ins. diam., bears S. 49* W., 35 lks. dist., mkd. T 29 S R 4 E S 23 B T.</p> <p>A fir, 9 ins. diam., bears N. 12* W., 7 lks. dist., mkd. T 29 S R 4 E S 14 B T.</p> <p>Land, mountainous. Soil, sandy loam and rocky, 2nd to 4th rate. Timber, fir, pine, hemlock, and larch. Undergrowth, alder, willow, small fir, pine, and hemlock.</p> <hr/> <p>N. 89*51' E., on a random line bet. secs. 13 and 24.</p>
40.00	Set temp. 1/4 sec. cor.
79.72	Intersect E. bdy. of the township 34 lks. N. of the cor. of secs. 13, 18, 19 and 24.
	Thence
	N. 89*54' W., on a true line, bet. secs. 13 and 24.
	Desc. 480 ft. over rocky SW. and W. slopes, through heavy timber and light undergrowth.
31.00	Foot of steep desc., leave rocks and heavy timber; thence over nearly level land, through small timber.
39.86	Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in. the ground, for 1/4 sec. cor., with brass cap mkd.
	$\frac{1}{4} \begin{array}{r} S 13 \\ \hline S 24 \\ 1930 \end{array}$
	from which
	A fir, 8 ins. diam., bears N. 18 1/2* E., 39 lks. dist., mkd. 1/4 S 13 B T.
	A fir, 9 ins. diam., bears S. 1* W., 35 lks. dist., mkd. 1/4 S 24 B T.
	Desc. 100 ft. over W. slope to
66.00	Desc. 100 ft. over NW. slope.