

County Surveyor's Record, Douglas County, Oregon

Township 29 South, Range 4 East.

Subdivision.

CHAINS

T 29 S | R 4 E
 S 11 | S 12
 S 14 | S 13
 1930

from which

- A cedar, 20 ins. diam., bears N. 49* E., 162 lks.
 dist., mkd. T 29 S R 4 E S 12 B T.
- A fir, 24 ins. diam., bears S. 34* E., 55 lks.
 dist., mkd. T 29 S R 4 E S 13 B T.
- A fir, 7 ins. diam., bears S. 18 $\frac{1}{2}$ * W., 76 lks.
 dist., mkd. T 29 S R 4 E S 14 B T.
- A fir, 6 ins. diam., bears N. 44* W., 47 lks.
 dist., mkd. T 29 S R 4 E S 11 B T.

Land, rolling and rolling mountainous.

Soil, sandy loam, 2nd rate.

Timber, fir, pine, hemlock, and cedar.

Undergrowth, small fir, pine, and hemlock.

S. 89*54' E., on a random line bet. secs. 12 and 13.

40.00 Set. temp. $\frac{1}{4}$ sec. cor.

79.96 Intersect E. bdy. of the township 5 lks. S. of the
 cor. of secs. 7, 12, 13, and 18.

Thence

N. 89*56' W., on a true line, bet. secs. 12 and 13.

Desc. 295 ft. over SW. slope to $\frac{1}{4}$ sec. cor., through
 scattering large timber and dense undergrowth.

39.98 Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in
 the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$ S 12
 S 13
 1930

from which

- A fir, 24 ins. diam., bears S. 37* W., 104 lks.
 dist., mkd. $\frac{1}{4}$ S 13 B T.