

## County Surveyor's Record, Douglas County, Oregon

Township 29 South, Range 4 East.

Subdivision.

## CHAINS

- 73.00 Top of bank; thence over rolling land.  
 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 32 ins. in the ground, for cor. of secs. 1, 2, 11, and 12, with brass cap mkd.

T 29 S	R 4 E
S 2	S 1
S 11	S 12
1930	

from which

- A pine, 10 ins. diam., bears N. 79\* E., 17 lks. dist., mkd. T 29 S R 4 E S 1 B T.  
 A fir, 10 ins. diam., bears S. 23\* E., 32 lks. dist., mkd. T 29 S R 4 E S 12 B T.  
 A fir, 10 ins. diam., bears S. 50\* W., 49 lks. dist., mkd. T 29 S R 4 E S 11 B T.  
 A fir, 15 ins. diam., bears N. 51\* W., 23 lks. dist., mkd. T 29 S R 4 E S 2 B T.

Land, mountainous and rolling.

Soil, sandy loam and rocky, 2nd to 4th rate.

Timber, fir, pine, hemlock, larch, and cedar.

Undergrowth, mountain laurel, chinquapin, small fir, pine, and hemlock.

- 
- S. 89\*56' E., on a random line bet. secs. 1 and 12.  
 40.00 Set temp.  $\frac{1}{4}$  sec. cor.  
 79.86 Intersect E. bdy. of the township 26 lks. S. of the cor. of secs. 1, 6, 7, and 12.

Thence

- S. 89\*53' W., on a true line, bet. secs. 1 and 12.  
 Desc. 45 ft. over SW. slope, through medium timber and medium undergrowth.  
 6.42 Creek, 6 lks. wide, course NW.; asc. 40 ft. over NE. slope.  
 14.50 Top of asc. on N. slope; desc. 175 ft. over NW. slope to  
 39.93 Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in