

County Surveyor's Record, Douglas County, Oregon

Township 29 South, Range 4 East.

Subdivision.

CHAINS

the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
$$\frac{1}{4} \frac{S 1}{S 12}$$
 1930

from which

A fir, 12 ins. diam., bears S. 24* E., 10 lks.

dist., mkd. $\frac{1}{4}$ S 12 B T.

A larch, 12 ins. diam., bears N. 73* W., 44 lks.

dist., mkd. $\frac{1}{4}$ S 1 B T.

Desc. 140 ft. over NW. slope.

51.50 Foot of steep desc.; thence over rolling land to

79.86 The cor. of secs. 1, 2, 11, and 12.

Land, rolling and mountainous.

Soil, sandy loam and rocky, 2nd to 4th rate.

Timber, fir, pine, and hemlock.

Undergrowth, small fir, pine, and hemlock.

 N. 0*01' W., on a random line bet. secs. 1 and 2.
40.00 Set temp. $\frac{1}{4}$ sec. cor.80.31 Intersect N. bdy. of the township 16 lks. E. of the
cor. of secs. 1, 2, 35, and 36.

Thence

S. 0*08' E., on a true line bet. secs. 1 and 2.

Over rolling land, through heavy timber and medium
undergrowth.

5.55 Diamond Lake Road, bears E. and SW.

8.00 Desc. 90 ft. over S. slope.

12.68 Draw, drains W.; asc. 175 ft. over NW. slope.

19.75 Spur, bears W.; desc. 350 ft. over broken S. slope to

40.31 Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in
the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.