

County Surveyor's Record, Douglas County, Oregon

Township 29 South, Range 4 East.

Subdivision.

CHAINS

A fir, 12 ins. diam., bears S. 12* W., 97 lks.
dist., mkd. T 29 S R 4 E S 15 B T.

A fir, 30 ins. diam., bears N. 45* W., 22 lks.
dist., mkd. T 29 S R 4 E S 15 B T.

Land, rolling and mountainous.

Soil, sandy and gravelly loam and rock, 2nd to 4th rate.

Timber, fir, pine, hemlock, and cedar.

Undergrowth, salal and huckleberry.

East, on a random line bet. secs. 14 and 23.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

80.20 Intersect N. and S. line 9 lks. N. of the cor. of secs.
13, 14, 23, and 24.

Thence

N. 89*56' W., on a true line, bet. secs. 14 and 23.

Desc. 50 ft. over SW. slope, through medium timber and
medium undergrowth.

3.75 Trail, bears S. and NW.

4.10 Gully, drains S.; asc. 35 ft. over SE. slope.

4.33 Trail, bears NE. and SW.

5.35 Top of asc.; desc. 50 ft. over rolling W. slope to $\frac{1}{4}$
sec. cor.

7.73 Trail, bears NW. and SE.

40.10 Set an iron post, 3 ft. long, 1 in. diam., 32 ins. in
the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

S 14
 $\frac{1}{4}$ —————
S 23
1930

from which

A pine, 18 ins. diam., bears S. 32* W., 42 lks.
dist., mkd. $\frac{1}{4}$ S 23 B T.

A fir, 14 ins. diam., bears N. 14* W., 106 lks.
dist., mkd. $\frac{1}{4}$ S 14 B T.