

## County Surveyor's Record, Douglas County, Oregon

Township 29 South, Range 4 East.

Subdivision.

CHAINS

Asc. 280 ft. over S. slope.

58.25 Spur, bears W.; desc. 540 ft. over NW. slope to

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for cor. of secs. 10, 11, 14, and 15, with brass cap mkd.

T 29 S	R 4 E
S 10	S 11
S 15	S 14
1930	

from which

A hemlock, 26 ins. diam., bears N. 28\* E., 75 lks. dist., mkd. T 29 S R 4 E S 11 B T.

A fir, 20 ins. diam., bears S. 32\* E., 54 lks. dist., mkd. T 29 S R 4 E S 14 B T.

A fir, 16 ins. diam., bears S. 57\* W., 71 lks. dist., mkd. T 29 S R 4 E S 15 B T.

A hemlock, 26 ins. diam., bears N. 20\* W., 34 lks. dist., mkd. T 29 S R 4 E S 10 B T.

Land, rolling and mountainous.

Soil, sandy and gravelly loam and rocky, 2nd to 4th rate.

Timber, fir, pine, hemlock, and cedar.

Undergrowth, mountain laurel, willow, small fir, pine, and hemlock.

---

S. 89\*56' E., on a random line bet. secs. 11 and 14.

40.00 Set temp.  $\frac{1}{4}$  sec. cor.

80.04 Intersect N. and S. line 5 lks. S. of the cor. of secs. 11, 12, 13, and 14.

Thence

N. 89\*58' W., on a true line, bet. secs. 11 and 14.

Desc. 25 ft. over SW. slope, through scattering timber and dense undergrowth.

12.00 Foot of desc. on S. slope; asc. 35 ft. over SE. slope.