

## County Surveyor's Record, Douglas County, Oregon

Township 29 South, Range 4 East.

Subdivision.

CHAINS

$$\begin{array}{c} \frac{1}{4} \\ | \\ \text{S } 10 | \text{S } 11 \\ | \\ 1930 \end{array}$$

from which

A fir, 9 ins. diam., bears S. 43\* E., 28 lks.

dist., mkd.  $\frac{1}{4}$  S 11 B T.A pine, 28 ins. diam., bears N. 17 $\frac{1}{2}$ \* W., 47 lks.dist., mkd.  $\frac{1}{4}$  S 10 B T.

Asc. 60 ft. to sec. cor.

- 47.30 Rogue River, 65 lks. wide, course SW.  
 51.30 Rogue River, 60 lks. wide, course SE.  
 59.00 Rogue River, 60 lks. wide, course SW.  
 65.60 Rogue River, 50 lks. wide, course SE.  
 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 12 ins. in the ground, to rock, and build a mound of stone, 4 ft. base, 1 $\frac{1}{2}$  ft. high, around the post, for cor. of secs. 2, 3, 10, and 11, with brass cap mkd.

$$\begin{array}{c} \text{T } 29 \text{ S } | \text{R } 4 \text{ E} \\ \text{S } 3 \text{ S } 2 \\ \hline \text{S } 10 | \text{S } 11 \\ \cdot \\ 1930 \end{array}$$

from which

A pine, 16 ins. diam., bears N. 64\* E., 72 lks.

dist., mkd. T 29 S R 4 E S 2 B T.

A fir, 18 ins. diam., bears S. 29\* E., 95 lks.

dist., mkd. T 29 S R 4 E S 11 B T.

A fir, 14 ins. diam., bears S. 26\* W., 23 lks.

dist., mkd. T 29 S R 4 E S 10 B T.

A pine, 36 ins. diam., bears N. 40\* W., 108 lks.

dist., mkd. T 29 S R 4 E S 3 B T.

Land, mountainous and rolling.

Soil, sandy loam, peat, and rocky, 2nd to 4th rate.

Timber, fir, pine, hemlock, and cedar.