

County Surveyor's Record, Douglas County, Oregon

Township 29 South, Range 4 East.

Subdivision.

CHAINS

T 29. S	R 4 E
S 28	S 27
S 33	S 34
1930	

from which

A fir, 16 ins. diam., bears N. 62* E., 51 lks.
dist., mkd. T 29 S R 4 E S 27 B T.

A fir, 10 ins. diam., bears S. 22* E., 107 lks.
dist., mkd. T 29 S R 4 E S 34 B T.

A fir, 20 ins. diam., bears S. 23½* W., 87 lks.
dist., mkd. T 29 S R 4 E S 33 B T.

A fir, 28 ins. diam., bears N. 49* W., 75 lks.
dist., mkd. T 29 S R 4 E S 28 B T.

Land, rolling and mountainous.

Soil, sandy and gravelly loam and rocky, 2nd to 4th rate.

Timber, fir, pine, hemlock, and larch.

Undergrowth, chinquapin, huckleberry, small fir, pine,
and hemlock.

East, on a random line bet. secs. 27 and 34.

40.00 Set temp. ¼ sec. cor.

79.54 Intersect N. and S. line 14 lks. N. of the cor. of
secs. 26, 27, 34, and 35.

Thence

N. 89*54' W., on a true line, bet. secs. 27 and 34.

Desc. 290 ft. over NW. slope to ¼ sec. cor., through
medium timber and medium undergrowth.

39.77 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in
the ground, for ¼ sec. cor., with brass cap mkd.

¼	S 27
	S 34
1930	

from which