

County Surveyor's Record, Douglas County, Oregon

Township 29 South, Range 4 East.

Subdivision.

CHAINS

74.00 A low spur, bears W.; desc. 25 ft. over N. slope to  
 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in  
 the ground, for cor. of secs. 21, 22, 27, and 28, with  
 brass cap mkd.

T 29 S	R 4 E
S 21	S 22
S 28	S 27
1930	

from which

- A fir, 16 ins. diam., bears N.  $49\frac{1}{2}^*$  E., 54 lks.  
dist., mkd. T 29 S R 4 E S 22 B T.
- A fir, 12 ins. diam., bears S.  $16^*$  E., 32 lks.  
dist., mkd. T 29 S R 4 E S 27 B T.
- A fir, 20 ins. diam., bears S.  $39\frac{1}{2}^*$  W., 45 lks.  
dist., mkd. T 29 S R 4 E S 28 B T.
- A fir, 12 ins. diam., bears N.  $53^*$  W., 93 lks.  
dist., mkd. T 29 S R 4 E S 21 B T.

Land, mountainous.

Soil, sandy and gravelly loam and rocky, 2nd to 4th rate.

Timber, fir, pine, hemlock, and larch.

Undergrowth, chinquapin, mountain laurel, small fir,  
pine, and hemlock.

S.  $89^*54'$  E., on a random line bet. secs. 22 and 27.  
 40.00 Set temp.  $\frac{1}{4}$  sec. cor.  
 79.54 Intersect N. and S. line 25 lks. S. of the cor. of  
 secs. 22, 23, 26, and 27.

Thence

S.  $89^*55'$  W., on a true line, bet. secs. 22 and 27.  
 Desc. 120 ft. in creek bottom, through medium timber  
 and medium undergrowth.

4.90 Creek, 5 lks. wide, course SW.