

County Surveyor's Record, Douglas County, Oregon

Township 29 South, Range 4 East.

Subdivision.

CHAINS

40.00 Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$
 S 21 | S 22
 1930

from which

A fir, 9 ins. diam., bears S. 11* E., 23 lks. dist., mkd. $\frac{1}{4}$ S 22 B T.

A fir, 20 ins. diam., bears S. 77 $\frac{1}{2}$ * W., 75 lks. dist., mkd. $\frac{1}{4}$ S 21 B T.

44.00 Desc. 130 ft. over N. slope.

46.40 National Creek, 30 lks. wide, course West; asc. 135 ft. over S. slope.

53.20 Spur, bears W.; desc. 60 ft. over N. slope.

59.50 Creek, 1 lk. wide, course SW.; asc. 55 ft. over SE. slope.

67.65 Diamond Lake Road and top of asc., bears NE. and SW.; thence over level land.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, for cor. of secs. 15, 16, 21, and 22, with brass cap mkd.

T 29 S | R 4 E
 S 16 | S 15
 S 21 | S 22
 1930

from which

A pine, 8 ins. diam., bears N. 42* E., 83 lks. dist., mkd. T 29 S R 4 E S 15 B T.

A pine, 10 ins. diam., bears S. 44* E., 45 lks. dist., mkd. T 29 S R 4 E S 22 B T.

A pine, 10 ins. diam., bears S. 68* W., 5 lks. dist., mkd. T 29 S R 4 E S 21 B T.

A pine, 10 ins. diam., bears N. 55* W., 25 lks. dist., mkd. T 29 S R 4 E S 16 B T.

Land, mountainous, rolling, and level.