

County Surveyor's Record, Douglas County, Oregon

Township 29 South, Range 4 East.
Subdivision.

CHAINS


Land; rolling.
Soil; sandy loam and rocky, 2nd to 4th rate.
Timber; fir, pine, hemlock, and larch.
Undergrowth; mountain laurel, willow, small fir, pine,
and hemlock.

From the cor. of secs. 4, 5, 32, and 33, on S. bdy. of
the township, which is an iron post, 2 ins. diam.,
6 ins. above ground, with brass cap marked and wit-
nessed as described in the field notes of T. 30 S.,
R. 4 E.

N. 0*03' W., bet. secs. 32 and 33.

Asc. 10 ft. over SW. slope, through medium timber and
medium undergrowth.

- 1.70 Spur, bears W., desc. 65 ft. over NW. slope.
- 5.60 Draw, drains W., asc. 85 ft. over S. slope.
- 9.70 Spur, bears W., desc. 110 ft. over NW. slope.
- 13.75 Creek, 12 lks. wide, course W., asc. 110 ft. over
broken S. slope.
- 31.00 Top of asc., bears E. and W., desc. slightly to
- 40.00 Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in
the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked.



from which,

- A pine, 24 ins. diam., bears S. 23 * E., 45 lks.
dist., marked $\frac{1}{4}$ S 33 B T
- A fir, 18 ins. diam., bears S. 10*W., 56 lks.
dist., marked $\frac{1}{4}$ S 32 B T.

Thence over nearly land.

- 51.00 Desc. 150 ft. over NW. slope.