

## County Surveyor's Record, Douglas County, Oregon

Township 29 South, Range 4 East.  
Subdivision.

CHAINS

medium undergrowth.

- 4.00 Desc. 335 ft. over NW. slope.
- 38.50 National Creek, 33 lks. wide, course SW.; thence over a brushy bar, in creek botton.
- 39.85 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap marked.

$$\frac{1}{4} \begin{array}{l} S 21 \\ S 28 \\ 1930 \end{array}$$

from which,

A fir, 12 ins. diam., bears S. 76\* W., 63 lks. dist., marked  $\frac{1}{4}$  S 28 B T.

A hemlock, 14 ins. diam., bears N. 37\* W., 31 lks. dist., marked  $\frac{1}{4}$  S 21 B T.

- 40.50 Asc. 175 ft. over SE. slope, through dense undergrowth.
- 44.50 Top of asc.; thence over nearly level land.
- 45.00 Diamond Lake Road, bears NE. and SW.
- 62.00 A dim road, bears NW. and SE.
- 79.70 The cor. of secs. 20, 21, 28, and 29.

Land; mountainous and rolling.

Soil; sandy and gravelly, 2nd rate.

Timber; fir, pine, and hemlock.

Undergrowth, mountain laurel, alder, chinquapin, small fir, pine, and hemlock.

---

N. 0\*03' W., bet. secs. 20 and 21,

Asc. 30 ft. over rolling land, through medium timber and dense undergrowth.

- 34.00 Desc. 80 ft. over N. slope to
- 40.00 Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap marked.

$$\frac{1}{4} \begin{array}{l} S 20 | S 21 \\ 1930 \end{array}$$