

County Surveyor's Record, Douglas County, Oregon

10931
21

Township 29 South, Range 4 East.
Subdivision.

CHAINS

Soil; sandy and gravelly loam, 2nd and 3rd rate.
Timber; fir, pine, and hemlock.
Undergrowth; mountain laurel, willow, small fir, pine,
and hemlock.

N. 0°03' W., bet. secs. 16 and 17.

Desc. 65 ft. over NE. slope, through medium timber
and dense undergrowth.

7.25 Draw, drains SE., asc. 225 ft. over broken SE. slope to
40.00 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in
the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked.

$$\begin{array}{c} \frac{1}{4} \\ \text{S } 17 \text{ | S } 16 \\ \hline 1930 \end{array}$$

from which,

A fir, 24 ins. diam., bears S. 12° E., 48 lks.
dist., marked $\frac{1}{4}$ S 16 B T.

A fir, 24 ins. diam., bears N. 83° W., 81 lks.
dist., marked $\frac{1}{4}$ S 17 B T.

Thence over broken E. slope.

62.30 Creek, 6 lks. wide, course SE.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 32 ins. in
the ground, for cor. of secs. 8, 9, 16, and 17, with
brass cap marked

$$\begin{array}{c} \text{T } 29 \text{ S | R } 4 \text{ E} \\ \text{S } 8 \text{ | S } 9 \\ \hline \text{S } 17 \text{ | S } 16 \\ 1930 \end{array}$$

from which,

A fir, 20 ins. diam., bears N. 9° E., 102 lks.
dist., marked T 29 S R 4 E S 9 B T.

A fir, 15 ins. diam., bears S. 60 $\frac{1}{2}$ ° E., 100 lks.
dist., marked T 29 S R 4 E S 16 B T.

A fir, 36 ins. diam., bears S. 23° W., 57 lks.